

48" Gas Rangetops

Wolf gas rangetops offer that professional look but give you the flexibility to use ovens in other locations in the kitchen. Wolf gas rangetops offer standard features such as dual brass surface burners and our signature large red control knobs. Optional infrared charbroiler and infrared griddle give you the freedom to customize your gas rangetop. Wolf gas rangetops are available in natural or LP gas.





Model RT488



Model RT486C



Model RT486G



Model RT484CG



Model RT484DG

FEATURES

- Stainless steel exterior finish.
- Optional infrared charbroiler and infrared griddle configurations.
- Distinctive red control knobs with chrome bezels — black knobs optional.
- Dual brass burners with automatic reignition at all settings.
- · Porcelain-coated cast iron grates.
- Stainless steel drip tray.

FEATURES

Model	RT488	RT486C	RT486G	RT484CG	RT484DG
Surface Burners 16,000 Btu / 500 Btu simmer	8	6	6	4	4
Infrared Charbroiler - 16,000 Btu		•		•	
Infrared Griddle - 18,000 Btu			•	•	
Double Griddle - 18,000 Btu (2)					•

Model numbers are for natural gas rangetops, add (-LP) to the model number for LP gas.

ACCESSORIES

- 10¹/₂" stainless steel riser.
- Black control knobs.
- 2 or 3 piece trim.
- Porcelain-coated cast iron wok grate.
- · Porcelain-coated cast iron S-grates.
- Hardwood cutting board (griddle models only).
- · Griddle cleaning kit.

Accessories are available through your authorized Wolf dealer. For local dealer information, visit the find a showroom section of our website, wolfappliance.com.

This appliance is certified by Star-K to meet strict religious regulations in conjunction with specific instructions found on www.star-k.org.





Infrared griddle.

Dual brass burner.

OVERALL DIMENSIONS

00



48" (1219)

6

101/2" (267)

TO COOKING SURFACE 91/2"


(241)

Unit dimensions may vary by $\pm 1/8$ ".

SPECIFICATIONS

Exterior Finish	Stainless Steel
Overall Width	48"
Overall Height (to cooking surface)	10 ¹ /2"
Overall Depth	271/4"
Opening Width	481/4"
Opening Height (to countertop)	91/2"
Opening Depth	24"
Electrical Requirements	110/120 V AC 60 Hz, 15 amp circuit
Shipping Weight	220-280 lbs

INSTALLATION SPECIFICATIONS



271/4" (692)

- 2³/4" (70)

241/2" (622)

25¹/4" (641)

2" (51)

20" (508) 10¹/₂"

RISER

- *Minimum clearance from rough opening to combustible materials up to 18" (457) above countertop.

 **36" (914) minimum clearance, 44" (1118) for charbroiler, from countertop to combustible materials without ventilation hood.
- $NOTE: For island \ installations, 12" (305) \ minimum \ clearance \ from \ back \ of \ rangetop \ to \ combustible \ rear \ wall \ above \ countertop.$

INSTALLATION NOTES

- A 10¹/₂" riser is required for installations against a combustible surface.
- A Wolf pro wall, chimney, island ventilation hood or hood liner is recommended.

Dimensions in parentheses are in millimeters unless otherwise specified.